



△	
△	
REVISION	

U.S. DEPARTMENT OF AGRICULTURE	FOREST SERVICE	SHOSHONE NATIONAL FOREST
		FILE No.


SHOSHONE NATIONAL FOREST	BROADAXE TIMBER SALE
--------------------------	----------------------

DESIGNED BY M. PRICE 1/16	DRAWN BY M. PRICE 1/16	CHECKED BY M. DE LA CRUZ 1/16
------------------------------	---------------------------	----------------------------------


SHEET TITLE STORMWATER DEFLECTOR DETAILS

SHEET NO. 8 OF 9

TYPICAL SURFACE WATER DEFLECTOR DETAILS ITEM 204(03)




INSTALLATION DETAIL



SINGLE LANE

VALUES FOR SKEWED INSTALLATION (FEET)

ROAD WIDTH	A	B
12	14	7.2
13	16	9.3
14	16	7.7
15	18	9.9
16	18	8.2
17	20	10.5
18	20	8.7



DOUBLE LANE

DRAWINGS NOT TO SCALE

NOTES

1. ALL TREATED LUMBER SHALL BE INCISED AND PRESSURE TREATED IN ACCORDANCE WITH THE AWPAC UC4-A FOR GROUND CONTACT.
2. FIELD TREATMENT: ALL ABRASIONS AND CUTS MADE IN THE FIELD SHALL BE CAREFULLY TRIMMED AND GIVEN THREE BRUSH COATS OF THE TREATMENT SOLUTION. HOLES DRILLED IN THE FIELD SHALL BE POURED FULL OF PRESERVATIVE AND PLUGGED WITH TIGHT FITTING TREATED PLUGS.
3. ALL HARDWARE SHALL CONFORM TO FP-03 716.02 AND SHALL BE GALVANIZED. LUMBER SHALL CONFORM TO FP-03 716.03.
4. OUTLET OF DEFLECTOR SHALL BE A MINIMUM OF 0.5' LOWER THAN THE INLET.
5. CERTIFICATIONS: ONE COPY OF THE FOLLOWING COMPLIANCE CERTIFICATE SHALL BE FURNISHED UPON DELIVERY OF THE MATERIALS:
 - A. SUPPLIER CERTIFICATION THAT ALL WOOD MATERIALS MEET THE REQUIREMENTS AS TO SPECIES AND GRADE.
 - B. CERTIFICATION OF TREATMENT OF LUMBER TO INCLUDE TYPE OF PRESERVATIVE, RETENTION IN PCF (ASSAY METHOD) AND PENETRATION IN INCHES, BY A QUALIFIED INSPECTION AND TESTING AGENCY.
 - C. SUPPLIER CERTIFICATION THAT ALL RUBBER BELTING MATERIALS MEET THE REQUIREMENTS AS NOTED IN DETAIL.